
# **Decra® Stratos L**




### Design



Overall Length*	1340 mm
Length of Cover*	1262 mm
Overall Width*	415 mm
Width of Cover/ Batten space	369 mm
Minimum pitch	12° (21 %)
Maximum pitch	90°
Roof Cover*	0.47 m <sup>2</sup>
Tiles per m²	2.15
Weight/panel	3.10 kg
Weight/area	6.66 kg/m²

<sup>\*</sup> The measurements and the weight may vary slightly by the finish that is added to the accessory.

### **Material structure**



- 1 Transparent protection layer
- 2 Stone Chip
- 3 Basecoat
- 4 Transparent Acrylic Coating
- **5** Aluminium-Zinc alloy
- 6 Stee
- **7** Aluminium-Zinc alloy
- 8 Transparent Acrylic Coating

## Steel specification

The DECRA STRATOS L tile is made of Aluminium-Zinc alloy coated steel. The grade of steel used is designed to allow forming without cracking or significant elastic recovery and at the same time to be rigid enough to tolerate reasonable loads without excessive deformation.

Steel Thickness	0.43 mm
Steel Grade	S280GD
	G300
Aluminium-Zinc Coating Mass	150 g/m²
Aluminium-Zinc Coating Grade	AZ150

### **Textured surface**

Stone chip granules are applied to provide an attractive textured finish which at the same time enhance resistance to UV radiation. Granules are ceramic coated with lightfast heat resistant pigments.

### **Coating specification**

**Transparent protection layer:** Clear 100% acrylic resin coating for granule binding and a semi-gloss finish. It helps enhance the appearance as well as increase the resistance to physical damage.

**Stone Chip:** Carefully selected granules provide excellent surface coverage and attractive natural looking and lasting colours.

**Basecoat:** A tough opaque coating based on acrylic resin. It bonds the stone chips and protects the underlying layer from water and UV radiation. It has good UV resistance and retains its flexibility although it does become harder after the first few weeks.

**Transparent coatings:** Both sides of the Aluminium-Zinc alloy coated steel are coated with a transparent layer that provides protection and a uniform substrate for further coatings. This transparent coating allows identification of the Aluminium-Zinc substrate to be made by distributors and customers.

#### Colour

